


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

| | | |
|--|-----------|--|
| (51) International Patent Classification ⁶: G10H 3/18, H01F 27/36 | A1 | (11) International Publication Number: WO 99/39332 (43) International Publication Date: 5 August 1999 (05.08.99) |
| (21) International Application Number: PCT/US99/01605 (22) International Filing Date: 26 January 1999 (26.01.99) (30) Priority Data: 09/014,839 28 January 1998 (28.01.98) US (71) Applicant: FENDER MUSICAL INSTRUMENTS CORPORATION [US/US]; 2975 North Hayden Road, Scottsdale, AZ 85258 (US). (72) Inventor: TURNER, William, T.; 2400 Ridgeview Drive #212, Chino Hills, CA 91710 (US). (74) Agents: WEIR, Jan, P. et al.; Oppenheimer Wolff & Donnelly LLP, Suite 3800, 2029 Century Park East, Los Angeles, CA 90067 (US). | | (81) Designated States: European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i> |

(54) Title: PICKUP FOR ELECTRIC GUITARS**(57) Abstract**

A pickup for a guitar is disclosed herein comprising an upper coil (14) wound longitudinally around an upper bobbin (10), a lower coil (15) wound longitudinally around a lower bobbin (11), and a ferromagnetic plate (17) longitudinally interposed between the lower and upper bobbins. The pickup further includes a plurality of magnetic pole pieces (12a-f) situated within respective vertical holes in the upper and lower bobbins and the ferromagnetic plate that extends from above the upper bobbin to the bottom of the lower bobbin. The ferromagnetic plate isolates the respective magnetic fields in the upper and lower bobbins to prevent phase cancellation at desired frequencies.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

| | | | | | | | |
|----|--------------------------|----|--|----|--|----|--------------------------|
| AL | Albania | ES | Spain | LS | Lesotho | SI | Slovenia |
| AM | Armenia | FI | Finland | LT | Lithuania | SK | Slovakia |
| AT | Austria | FR | France | LU | Luxembourg | SN | Senegal |
| AU | Australia | GA | Gabon | LV | Latvia | SZ | Swaziland |
| AZ | Azerbaijan | GB | United Kingdom | MC | Monaco | TD | Chad |
| BA | Bosnia and Herzegovina | GE | Georgia | MD | Republic of Moldova | TG | Togo |
| BB | Barbados | GH | Ghana | MG | Madagascar | TJ | Tajikistan |
| BE | Belgium | GN | Guinea | MK | The former Yugoslav Republic of Macedonia | TM | Turkmenistan |
| BF | Burkina Faso | GR | Greece | ML | Mali | TR | Turkey |
| BG | Bulgaria | HU | Hungary | MN | Mongolia | TT | Trinidad and Tobago |
| BJ | Benin | IE | Ireland | MR | Mauritania | UA | Ukraine |
| BR | Brazil | IL | Israel | MW | Malawi | UG | Uganda |
| BY | Belarus | IS | Iceland | MX | Mexico | US | United States of America |
| CA | Canada | IT | Italy | NE | Niger | UZ | Uzbekistan |
| CF | Central African Republic | JP | Japan | NL | Netherlands | VN | Viet Nam |
| CG | Congo | KE | Kenya | NO | Norway | YU | Yugoslavia |
| CH | Switzerland | KG | Kyrgyzstan | NZ | New Zealand | ZW | Zimbabwe |
| CI | Côte d'Ivoire | KP | Democratic People's Republic of Korea | PL | Poland | | |
| CM | Cameroon | KR | Republic of Korea | PT | Portugal | | |
| CN | China | KZ | Kazakhstan | RO | Romania | | |
| CU | Cuba | LC | Saint Lucia | RU | Russian Federation | | |
| CZ | Czech Republic | LI | Liechtenstein | SD | Sudan | | |
| DE | Germany | LK | Sri Lanka | SE | Sweden | | |
| DK | Denmark | LR | Liberia | SG | Singapore | | |
| EE | Estonia | | | | | | |

PICKUP FOR ELECTRIC GUITARS

BACKGROUND OF THE INVENTION

It is well known that a pickup consisting of a single monolithic coil will pick
5 up stray electromagnetic radiation and transmit this radiation (when coupled to a
musical instrument amplifier) in the form of noise, which is audible as low
frequency 60HZ hum. There is also electrostatic noise, in the form of high
frequency buzzing, at the pickup's resonant peak frequency. By combining a pair of
coils as employed in the humbucking pickup principle, the audible noise factor is
10 considerably reduced but not completely eliminated. As shown in U.S. Patent
4,442,749, the humbucking principle can be applied in a pickup with the coils
arranged in a concentric configuration, with a metal plate formed into a U shaped
channel common only to the upper coil section of the pickup. This configuration is
inductively unbalanced, which compromises the noise reduction capability of the
15 pickup.

SUMMARY OF THE INVENTION

The present invention in one of its aspects has symmetrically balanced coils
arranged in a concentric configuration, with a ferromagnetic steel plate centrally
20 common to both coils; it incorporates the humbucking pickup principle for
maximum noise immunity.

There is an improved means for increasing the volume of magnetic flux
through the coils of the pickup, which correspondingly increases the output voltage
and signal amplitude of the pickup.

25 There is an improved means for adding or subtracting inductive components
to enhance the sound and tonal characteristics of the pickup, without compromising
noise immunity.

There is an improved means for incorporating magnetic pole pieces of
varying length in the pickup to control the output, balance, and sensitivity for
30 varying diameter musical strings.

There is an improved means for increasing isolation between the pickup coils to reduce phase cancellation of common frequencies, which allows the pickup to exhibit an improved harmonic content for richer sound and tonal quality.

5 BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a top plan view of an electromagnetic pickup embodying the present invention;

Fig. 2 is a view, the right half of which is in side elevation and the left half of which is in vertical central section, of the pickup; and

10 Fig. 3 is an end elevation as viewed from the right in Fig. 1, the coils being unshown.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The illustrated embodiment is symmetrical about a vertical plane that is perpendicular to the longitudinal axis of the pickup and that is midway between the ends of the pickup.

The illustrated pickup is for a six-string electric guitar.

The core assembly of the pickup comprises an upper bobbin section, a centrally located ferromagnetic steel plate, and a lower bobbin section. Fastening screws, of ferromagnetic material, are inserted through the bobbin core at the base of the lower bobbin section. The fastening screws extend upward from the lower bobbin section. A central steel plate is provided with corresponding apertures to engage the fastening screws. The fastening screws may pass through the apertures in the plate, the apertures in the plate being of a greater diameter than the major diameter of the screw. The plate engages the upper planar surface of the lower bobbin section.

The fastening screws extend upward through the plate to receive the upper bobbin section. The upper bobbin section engages the plate at the lower planar surface of the upper bobbin section. The screws are then fastened into the upper bobbin section, coupling the upper and lower bobbin sections together with the plate

interposing the upper face section of the lower bobbin and the lower face section of the upper bobbin.

Each bobbin section has a plurality of circular apertures which extend and align through the central core of the upper and lower bobbin sections to receive a plurality of corresponding rod type magnetic pole pieces. The plate has a plurality of corresponding circular apertures which align with the circular apertures in the upper and lower bobbin sections.

The circular apertures in the plate have a plurality of smaller apertures adjacent to the circular apertures for the purpose of receiving the fastening screws and additional ferromagnetic steel pole pieces.

The magnetic pole pieces are of sufficient length to extend fully through the upper and lower bobbin sections.

The magnetic pole pieces are flush at the base of the lower bobbin section and extend upwardly through the upper bobbin, projecting a short distance above the upper bobbin section surface, being positioned above the upper bobbin surface in an echelon arrangement.

The pickup shown in the drawings comprises an upper bobbin 10, a lower bobbin 11, six permanent magnet pole pieces 12, screws 13, upper and lower windings 14 and 15, and a ferromagnetic steel plate 17.

Upper bobbin 10 and lower bobbin 11 are formed of nonmagnetic material and nonmagnetizable material, preferably a synthetic resin. Upper bobbin 10 has upper and lower plates between which the upper winding is wound in a particular direction, for example clockwise as viewed from above. These plates are identical to each other in the illustrated embodiment, although this is not necessary. Lower bobbin 11 has upper and lower plates also parallel to each other, the upper plate in the preferred form being much larger than the lower and forming a skirt which is used for mounting purposes. The upper and lower plates of upper bobbin 10 are numbered 18 and 19, respectively. The skirt plate and lower plate of lower bobbin 11 are numbered 20 and 21, respectively.

The six permanent magnet pole pieces 12a, 12b, 12c, 12d, 12e, 12f are mounted parallel to each other in registered holes in upper and lower bobbins 10 and

11, as shown. The magnetic poles of the pole pieces correspond to each other. Thus, for example, all of the north poles are uppermost and all of the south poles are lowermost.

5 The steel screws 13 are secured in internally threaded holes in the upper and lower bobbins 10,11, and not only hold the bobbins together with each other and with the ferromagnetic steel plate, but also alter the inductance of the pickup. Thus, they serve two purposes.

There are holes 23 in the bobbins, between pole pieces 12b and 12c, and 12d and 12e.

10 There are connections (Fig. 1) 27,28,29 and 30. Two of these serve the upper coil or winding 14, and the other two serve the lower winding 15. The lower winding is wound in the opposite direction from the upper, for example counterclockwise in the illustration. Thus, there is the humbucking effect.

15 The ferromagnetic steel plate 17 is sandwiched between plates 19 and 20 and parallel thereto, being formed of magnetizable material. Stated more definitely, element 17 is a ferromagnetic steel plate. The steel plate has clearance holes therethrough to receive the pole pieces and the screws.

20 It is to be understood that ferromagnetic cylinders may be inserted in the holes 23,24 in order to change the inductance of the pickup. These may be changed in accordance with the desires of the musician. Stated otherwise, there may be cylinders in some holes or openings 23,24 and not in others.

The foregoing detailed description is to be clearly understood as given by way of illustration and example only, the spirit and scope of this invention being limited solely by the appended claims.

What is claimed is:

CLAIMS:

1. (Amended) A pickup comprising:
 - (a) an upper bobbin being elongated along a longitudinal axis,
 - 5 (b) a lower bobbin being elongated along said longitudinal axis,
 - (c) permanent magnet pole pieces situated within holes in the upper and lower bobbins,
 - (d) screws holding said bobbins together,
 - (e) an upper winding,
 - 10 (f) a lower winding , and
 - (g) a non-magnetized ferromagnetic [steel] plate having opposing ends parallel to said longitudinal axis that terminate approximately below said upper winding, said plate being disposed between said bobbins and parallel thereto.
- 15 2. The pickup of claim 1, wherein the opposing ends of said ferromagnetic plate terminate approximately above said lower winding.
3. The pickup of claim 1, wherein the ferromagnetic plate includes steel.
- 20 4. The pickup of claim 1, further including ferromagnetic screws secured in internally threaded holes in one of said bobbins for holding the upper and lower bobbins together and altering the inductance of the pickup.
- 25 5. The pickup of claim 1, wherein said ferromagnetic screws include steel.
6. The pickup of claim 1, wherein said upper bobbin includes at least one hole for receiving a ferromagnetic cylinder for altering the inductance of the pickup.

7. A pickup comprising:
an upper bobbin elongated in a longitudinal axis;
an upper winding wound longitudinally around the upper bobbin;
a lower bobbin elongated in the longitudinal axis;
5 a lower winding wound longitudinally around the lower bobbin;
a non-magnetized ferromagnetic plate elongated in the longitudinal axis and interposed between and parallel to the upper and lower bobbins, said ferromagnetic plate including at least one end parallel to said longitudinal axis that terminates approximately below the upper winding; and
10 a magnetic pole piece extending orthogonal to the longitudinal axis from the upper bobbin to the lower bobbin and through respective openings in the upper bobbin, the ferromagnetic plate, and the lower bobbin.
8. The pickup of claim 7, further including a plurality of magnetic pole
15 pieces extending orthogonal to the longitudinal axis from the upper bobbin to the lower bobbin and through respective openings in the upper bobbin, the ferromagnetic plate, and the lower bobbin.
9. The pickup of claim 8, further including a pair of ferromagnetic
20 screws coupled to said bobbins for holding the bobbins together, said screws extending orthogonal to the longitudinal axis from the upper bobbin to the lower bobbin and through respective openings in the upper bobbin, the ferromagnetic plate, and the lower bobbin.
- 25 10. The pickup of claim 9, wherein the upper bobbin includes at least one opening extending from the top of the upper bobbin towards the lower bobbin for receiving therein a ferromagnetic cylinder for altering the inductance of the pickup.
11. The pickup of claim 10, wherein the upper bobbin includes upper and
30 lower plates that are elongated in the longitudinal axis, and wherein said lower plate abuts an upper surface of said ferromagnetic plate.

12. The pickup of claim 11, wherein the lower bobbin includes upper and lower plates that are elongated in the longitudinal axis, and wherein said upper plate of said lower bobbin abuts a lower surface of said ferromagnetic plate.

5 13. The pickup of claim 12, wherein the length of the second upper plate of the lower bobbin in the longitudinal direction is greater than the lower plate for forming a skirt plate.

10 14. A pickup comprising:
an upper coil;
a lower coil;
a flat non-magnetized ferromagnetic plate interposed between said upper and lower coils, said plate having ends terminating below said upper coil; and
a magnetic pole piece extending from the upper coil to the lower coil
15 through respective openings therein.

15. The pickup of claim 14, wherein said upper coil is wound around an upper bobbin.

20 16. The pickup of claim 14, wherein said lower coil is wound around a lower bobbin.




17. The pickup of claim 14, wherein the ends of said ferromagnetic plate terminates above the lower coil.

25

18. The pickup of claim 14, wherein the ferromagnetic plate includes steel.

19. The pickup of claim 14, further including a plurality of magnetic pole
5 pieces extending from the upper coil to the lower coil.

20. The pickup of claim 14, wherein the magnetic pole piece extends above the upper coil.



INTERNATIONAL SEARCH REPORT

International application No.
PCT/US99/01605

| A. CLASSIFICATION OF SUBJECT MATTER IPC(6) : G10H 3/18; H01F 27/36 US CL : 84/727,728; 336/84M, 110, 220 According to International Patent Classification (IPC) or to both national classification and IPC | | |
|---|---|--|
| B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) U.S. : 84/726-728; 336/84R, 84M, 110, 220, 221 Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched NONE Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) NONE | | |
| C. DOCUMENTS CONSIDERED TO BE RELEVANT | | |
| Category* | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
| X,P | US 5,834,999 A (KINMAN) 10 November 1998 (10/11/98), see the entire document. | 1-20 |
| <input type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex. | | |
| * "A" "B" "L" "O" "P" | Special categories of cited documents: document defining the general state of the art which is not considered to be of particular relevance earlier document published on or after the international filing date document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) document referring to an oral disclosure, use, exhibition or other means document published prior to the international filing date but later than the priority date claimed | "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "A" document member of the same patent family |
| Date of the actual completion of the international search 31 MARCH 1999 | | Date of mailing of the international search report 14 APR 1999 |
| Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231 Facsimile No. (703) 305-3230 | | Authorized officer STANLEY J. WITKOWSKI <i>Stanley J. Witkowski</i> Telephone No. (703) 308-1782 |